

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)


PCT

(10) International Publication Number
WO 2004/016545 A2

- (51) International Patent Classification⁷: **B67D 1/08**
- (21) International Application Number:
PCT/CA2003/001241
- (22) International Filing Date: 19 August 2003 (19.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 19 Feb 05
60/404,159 19 August 2002 (19.08.2002) US
- (71) Applicant (for all designated States except US): **ICE-FLOE TECHNOLOGIES INC.** [CA/CA]; 40 King Street West, Suite 5210, Scotia Plaza, Toronto, Ontario M5H 3Y2 (CA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CHIUSOLO, Sam** [CA/CA]; 96 John Street, Port Perry, Ontario L9L 1C4 (CA).
- (74) Agent: **KAPLAN, Adrian, M.**; Dimock Stratton Clarizio LLP, Suite 3202, Box 102, 20 Queen Street West, Toronto, Ontario M5H 3R3 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: **INLINE BOOSTER FOR BEVERAGE DISPENSING SYSTEM**



(57) Abstract: A beverage distribution system is provided for boosting the cooling capacity of conventional beer dispensing systems. This reduces the tendency of beer to foam prior to the dispensing of same. The beverage distribution system has a container for storing a beverage and a cooler for refrigerating the container and the beverage stored therein. The system also includes a beverage dispensing unit and a distribution line for delivering the beverage from the container to the dispensing unit. A trunk line extends substantially from or near the cooler to or near the dispensing tower. It includes the distribution line and a refrigerant line in an abutting relationship. The system has a heat transfer unit connected to the trunk line which is filled by refrigerant accumulating from the refrigerant line. The heat transfer unit has a coil connected to the distribution line for immersing a portion of the beverage in a bath of the refrigerant. A refrigeration loop circulates refrigerant through the heat transfer unit. Methods for chilling a beverage and reducing the foaming of beer using the beverage distribution system are also provided.